EXHIBIT 1

BOEING

Air Vehicle Configuration

Ed Barocela

IRD Requirements

Requirement	Threshold	Objective
Operating Airspeeds	up to 0.93 M @ 35 kft	up to 0.95 M @ 40 kft
Endurance	45 min @ 35 kft	60 min @ 35 kft
Loiter (Jammer)	30 min On-Station	40 min On-Station
Min. Rate of Climb	1500 fpm @ 25 kft	*Not Specified*
Turn Maneuverability	2 G's up to 19 kft	3 G's up 25 kft

BOEING

Meeting New Requirements

84 inch Body Length

Higher Speed and Endurance

Increased Body Fineness Ratio for Lower Drag and Higher Fuel Fraction

Flush Inlet

Higher Speed (Mach 0.93+)

External Pitot Inlet

Low Aspect Ratio Stub Wing

Higher Altitude and Endurance



Increase Wing Area and Aspect Ratio

BOEING

1st ALVIN Concept



- 7 Inch Diameter Circular Body
- 110 Inch Total Length
- Low Mounted Wing
  - Wing Fold Mechanism Outside of Fuel Tank
- High Aspect Ratio (AR = 8)
- External Pitot Inlet in Ventral Position

BOEING

Increase Fuel Fraction

"Grow" the Missile

- Current MALD is volume-limited compared to new IRD requirements
  - Fuel tank occupies largest fraction of fuselage length, yet
  - Fuel Fraction ~20%

81 inch length

110 inch length

BOEING

Increase Fuel Fraction

Non-Circular Cross Section Body

MALD
Circular cross section

Triangular
MACH/CALCM

Square
ITALD

Chined

BOEING

Increase Fuel Fraction

Re-Locate Engine Into External Nacelle



Raytheon *Streaker*

- Frees up fuselage internal volume for fuel
- External engine installations have been used on high speed drones (Mach No. > 0.9)

BOEING

Increase Aerodynamic Efficiency

Increase Wing Aspect Ratio



- Increase lift-to-drag ratio (L/D)
- Probably dictates high or low wing

BOEING

Alternate Wing: Option 1

Dual Position Wing

- First position used for high speed dash (lowest drag)
- Second position used for long endurance cruise and loiter (highest L/D)



Small Diameter Bomb (SDB)

Folding wing design is candidate for MALD

BOEING

Alternate Wing: Option 2

Oblique Wing

- First position used for high speed dash (lowest drag)
- Second position used for long endurance cruise and loiter (highest L/D)

Stowed Position

High Mach Cruise Position

Low Mach Loiter Position

BOEING

Alternate Wing: Option 3

Diamond Wing

- Innovative wing shape tested for Sensorcraft
- Aerodynamically equivalent to high aspect ratio wing
- Span can be reduced to eliminate need to fold wing
- More wing sections available for antenna placement

BOEING

Alternative Configurations



ALV-1  Circular cross section body
AR 8 wing

ALV-2  Triangular cross section body
AR 8 wing

ALV-3  Square cross section body
AR 8 wing

Alternative Configurations (cont.)

ALV-4

Circular cross section body
Diamondback wing

ALV-5

Circular cross section body
Oblique wing

Alternative Configurations (cont.)

ALV-6

Circular cross section body
Joined wing

ALV-7

Circular cross section body
AR 8 wing
External engine nacelle

BOEING

Trade Study Methodology

$$\text{Total Score} = \sum W_i U_i$$

Candidate Configuration Data

Cruise Speed
Endurance
Maneuverability
Weight
Fuel Fraction
Technical Risk

Utility Functions, u_i



Weighting Factors, w_i

iSIGHT

Parameter Sensitivity
Candidate Scores & Rankings

BOEING

ALVIN Utility Functions





BOEING

ALVIN Utility Functions





BOEING

ALVIN Utility Functions





BOEING

Technology Item: Unconventional Wing

Oblique Wing, Diamondback Wing, Joined Wing

Risk:

Unconventional wing performance will fall short of predictions

Consequences:

Performance shortfalls (speed, endurance)

Mitigation:

Wind tunnel measurements to validate aero code predictions. Carry alternative configuration through preliminary design phase as fall-back.



BOEING

Technology Item: Future Variant Evolution

Choice of Engine and Missile Diameter

Risk:

Future variants will require different engine installations to meet increased performance, payload and power requirements

Consequences:

Future variant designs will diverge from MALD baseline, will require significant re-design

Mitigation:

Conduct studies of future variants early.

Consider external or semi-recessed nacelle.



Trade Study Results

Candidate	Mach	Endurance	Maneuver	Weight	FF	Risk
ALV-1	0.99	55.3 min	2.7 g's	153 lb	27%	Medium
ALV-2	0.93	54.2 min	2.5 g's	161 lb	27%	Medium
ALV-3	0.90	59.6 min	2.4 g's	170 lb	29%	Medium
ALV-4	0.94	53.6 min	2.6 g's	164 lb	25%	High
ALV-5	1.00	59.1 min	2.7 g's	153 lb	27%	High
ALV-6	0.99	55.4 min	2.7 g's	152 lb	27%	High
ALV-7	0.97	67.6 min	2.6 g's	165 lb	31%	Low

BOEING

iSIGHT Analysis: Utility Function Sensitivities



Trade Study Scores*

Candidate	Total	Rank
ALV-7	4.69	1
ALV-1	4.04	2
ALV-5	3.62	3
ALV-6	3.56	4
ALV-2	3.40	5
ALV-4	3.02	6
ALV-3	2.95	7

Weight Factors = 1

Candidate	Total	Rank
ALV-7	4.91	1
ALV-1	4.69	2
ALV-5	4.65	3
ALV-6	4.57	4
ALV-4	3.72	5
ALV-2	3.48	6
ALV-3	2.42	7

Pareto Weight Factors

Maximum Possible Score = 6

BOEING

Preferred Concept Candidates

ALV-7

External Nacelle

ALV-1

Benchmark Configuration

ALV-5

Oblique Wing
(may require bifurcated inlet)

BOEING

Automated Missile Synthesis (AMS)

- Workstation-based synthesis tool
- Methodologies used in related codes (LODST, AVIS)



BOEING

Configuration Development



BOEING

ALVIN Preferred Concept

- Preferred Concept Design
- Preferred Concept Performance
- Manufacturing Approach
- Risk Mitigation

BOEING

Design Modifications

- Bifurcated Inlets
- Scarfed Inlet Face
- "Y-Tail" Empennage
- Planform-Aligned Fins
- 100 lb_f Thrust Class Engine



BOEING

Preferred Concept



BOEING

Internal Components



BOEING

Weight Statement

ITEM	EQUIPMENT	STRUCTURE	FUEL	TOTAL
Body		26.8 lb		26.8 lb
Wing		2.0 lb		2.0 lb
Horizontal Tail		0.6 lb		0.6 lb
Vertical Tail		2.3 lb		2.3 lb
Wing Fold		0.8 lb		0.8 lb
Bifurcated Inlets		4.4 lb		4.4 lb
Payload	10.0 lb	2.4 lb		12.4 lb
Avionics	15.0 lb	3.1 lb		18.1 lb
Fuel Tank	1.0 lb	6.9 lb	40.7 lb	48.5 lb
Miscellaneous	8.0 lb	2.1 lb		10.1 lb
Actuators	5.0 lb	1.5 lb		6.5 lb
Growth	2.0 lb	0.8 lb		2.8 lb
INLET	1.2 lb	0.6 lb		1.8 lb
ENGINE	26.8 lb	4.5 lb		31.3 lb
TOTALS	69.0 lb	58.9 lb	40.7 lb	168.6 lb

"Worst Case" with Heaviest Engine and Actuators

BOEING

Bomb Rack Integration Issue



FRONT VIEW

This Front View Shows the MALD Mounted on the 16S1710 C/D Pylon/MAU-12 Station 3 Is Shown With Station 7 Being Identical

BOEING

Small Diameter Bomb Sway Brace Extenders



AIR LAUNCHED VEHICLE INVESTIGATION

BOEING

Strake Definition



BOEING

MAU-12 Attachment with Body Strake



BOEING

B-1B Reduced Loadout

MALDS Mounted on Stations C11, C12, C21, C22 and C23 to the Bay FWD Bulkhead, Interference Detected



AFT BAY SHOWN

This View Shows the MALDS Mounted on All Locations of the 10 Station BRA in the Aft Weapons Bay. The Aft Weapons Bay Was Used Because it Represents the Smallest Envelope, However, the Same Results Would Be Experienced in the Forward and Intermediate Weapons Bays. Aircraft Not Shown for Clarity.

BOEING

F-15E Reduced Loadout



Station 5 MALD Has the Same Tail Fins to Pylon Interference Detected that Is Evident on stations 2, 8 and the CFT's

Configuration "A" and "B" Is shown in This Image With the Boeing MALD Concept Loaded Onto stations LC1, LC2 and LC3. Notice 2 Circled Areas Where There Is Some Major Interference Detected!

Loadout Improvement Options

- Shorten Nose Cone
  - Replace Conic Ogive Profile With Sears-Haack Profile to Reduce Drag
- Choose Compact Engine to Shorten Boattail
  - Example: TJ-50M

NOTE: launch lugs may straddle CG by ± 3 inches

BOEING

Shortened Missile

Original Nose-Lug Distance = 55.1”



Air Vehicle

- Preferred Concept Design
- Preferred Concept Performance
- Manufacturing Approach
- Risk Mitigation

BOEING

Vehicle Performance



* maximum altitude = 35,000 ft

BOEING

Performance (cont.)



Operating Airspeed = Mach 0.8

BOEING

Vehicle Performance



BOEING

Performance (cont.)

Maximum Endurance at 3,000 ft



Operating Airspeed = Mach 0.55

Decoy Mission Profile



BOEING

Decoy Reference Mission Performance





BOEING

Jammer Mission Profile



BOEING

Jammer Mission Performance



Optimum Loiter Speed
Teledyne Engines: Mach 0.62
TJ-50M: Mach 0.65-0.70

BOEING

Radar Cross Section

- Analysis Performed on "All-metal" Representation of Missile
  - VHF, UHF, L, S, C, X and Ku Bands
  - 360º Sweep at Different Elevations
- Results Indicate That Design:
  - Will Meet Requirements of Primary Decoy Mission
  - Is Sufficiently Robust to Support Growth Missions

RCS (cont.)

- Several Design Features Will Degrade Radar Signature
  - Reflections From SAS Payload Through Radar-transparent Nose
  - Details of Engine Inlet Boundary Layer Diverter (Internal or External)
  - Body Strake

Air Vehicle

- Preferred Concept Design
- Preferred Concept Performance
- Manufacturing Approach
- Risk Mitigation

BOEING

Airframe Structure

11 Structural Airframe Components



Materials and Processes

Component	Material	Process
Nose Cone	Glass Fiber Filled Ultem	Injection Molding
Payload Bulkhead	Aluminum	High Speed Machining
Forward Body	Aluminum	Extruded Tube
Mid Body Forward Bulkhead	Aluminum	Casting
Mid Body	Aluminum	Casting
Aft Body	Aluminum	Casting
Boattail	Glass Vinylester	Compression Molding
Wing	Glass/Epoxy with Spindle Insert	Resin Transfer Molding
Vertical Tail Fin	Glass/Epoxy with Root Fitting	Resin Transfer Molding
Horizontal Tail Fins	Glass Fiber Filled Ultem with Spindle Insert	Injection Molding
Folding Lugs	Steel	Machining

Component Sizing Conditions

Component	Captive Carry	Ejection	Free Flight	Internal Pressure
Nose Cone	▤	▤	▤	
Payload Bulkhead	▤	▤	▤	
Forward Body	▤	▤	▤	
Mid Body Forward Bulkhead	▤	▤	▤	▤
Mid Body	▤	▤	▤	▤
Aft Body	▤	▤	▤	
Boattail	▤	▤	▤	
Wing			▤	
Vertical Tail Fin			▤	
Horizontal Tail Fins			▤	
Folding Lugs	▤			

BOEING

Preliminary Design Loads



(1) Maximum Hook Tension (2 places) = 2,000 lb_f
(2) Maximum Sway Brace Compression (4 places) = 2,000 lb_f
(3) Maximum Captive Carry Acceleration = 13 g's vertical, 22 g's total
(4) Ejection Acceleration = 16 g's
(5) Maximum Flight Acceleration = 3 g's

BOEING

Preliminary Body Bending Moments



Wing Construction

- Resin Transfer Molding Process Will Incorporate Low Band Dipole Antenna
- Materials
  - Glass/epoxy Skins
  - Foam Core
  - Steel Pivot Insert



BOEING

Nose Cone Construction



- No Re-entrant IML for Minimal Tooling
- MATL - Glass Filled Ultem
- Process - Injection Molding

BOEING

Payload Bulkhead



- MATL - Aluminum
- Process - High Speed Machining

Midbody Forward Bulkhead



MALD Midbody



BOEING

Inserted Components

Folding Lugs
Machined Steel

Horizontal Fins (2)
Glass Fiber Filled Ultem
With Root Insert



Vertical Fin
Glass/Epoxy Skins and Foam Core
With Antenna and Root Insert

Air Vehicle

- Preferred Concept Design
- Preferred Concept Performance
- Manufacturing Approach
- Risk Mitigation

Air Vehicle Risk Items

- 1E: Design May Not Be Flexible Enough to Meet Requirement Creep
- 1F: Design May Not Be Flexible Enough to Incorporate the Jammer Requirement

Spiral Growth Options

- Growth Volume Behind Nose
  - 235 in^3 (Excluding Start-up Battery*)
- Enlarge Wing
  - At Least 2x Current Planform Area
- Electric Wing Actuator
  - Continuously Vary Sweep Angle to Optimize for Endurance

* >50 in^3 Available Between Inlet Ducts to Relocate Start-up Battery (19 in^3)

BOEING

Enlarged Wing



- 1.5x Span (2.25x Planform Area)
- Increases Low Speed Loiter Endurance
- Decreases Maximum Operating Speed

BOEING

Enlarged Wing (cont.)



Tel305-B has enlarged wing

BOEING

Enlarged Wing (cont.)



Tel305-B now operates at 40 kft